

# marmix

## Horizontal Twin Auger Trailed Mixer Wagon

---

### Horizontal Mix:

- n° 2 bottom cutting and mixing augers
- n° 1 counterblade adjustable in height, between the two augers.

### Advantages:

- Use of any type of bale;
  - Reduced cutting time and high mixing efficiency;
  - Right mix and good final result in the homogeneity and softness of the TMR;
- 

### De-Silating Device:

- n°1 silage cutter (width 1650mm.), with high productivity and with 2 operating rotation movements for cutting and loading for a fast and more accurate loading procedure.

### Advantages:

- Thanks to its design and concept guarantees a fast and accurate loading of many different products leaving a clean and uniform silo;
  - The silage cutter reinforced knives with tungsten coating are placed with a cross order; in this way they guarantee a clean cut without damaging the fibre of the product.
- 

### Distribution:

- n° 2 direct central doors with chutes (both width 900mm), opt several discharge conveyors of different dimensions.

### Advantages:

- Safe and silent and with low maintenance;
  - Homogeneous and continuous discharge;
  - Various possibilities to comply with different requires.
- 

### Transmission to Augers:

- n° 1 gearbox in oil bath for bottom augers

### Advantages:

- Low power absorption and fuel consumption;
  - High reliability of the transmission system;
  - Low maintenance.
- 

### Safety:

- Machines in compliance with European regulation EN 703 and machine regulation 89/392 with user manual and safety accessories.
- All silage cutter machines are equipped with an electro-hydraulic safety clutch and appropriate safety devices (only UE).